



Smart drill stands for professionals

The 3<sup>rd</sup> generation of drill stands







New high quality telescopic drill stands with increased performance and flexibility enabling fast, smart and ergonomic operation.







#### Smart drill stands for professionals





To the four  $40^+$  och  $50^+$  drill stands with universal motor mounting also have Weka and  $\emptyset$  60 mm mounting plates as accessories.

# 40<sup>+</sup> Telescopic- and hand held drill stands

- Drill vertical, horizontal, at any angle or stitch drill without the need of anchoring
- Quick start-up, easy finish and no holes
- Drill carriage with universal motor mounting
- Crankable telescopic stanchion
- Toothed rack on outer stanchion tube
- Flex top with zero adjustment and bolt hole
- Solid base plate with optional splash guard
- Wheel set fits both base plates

Technical data -	40 <sup>+</sup> telescopic drill stand
Telescopic length (mm) Extension module (mm)	2050 - 3250 750
Max drill diameter (mm) Max stroke length (mm)	220 (vertical using <i>FlexSupport</i> *) 600
Rotation angle (°) Tilting angle (°)	360 - 70 to + 90 0 to 180
Weight (kg)	38 kg







### The 3<sup>rd</sup> generation of drill stands



50\* hand held drill stand with foldable wheel set and BackSupport\* accessory.



**50**<sup>+</sup> **drill stand** with toothed rack on both tubes eliminates heavy lifting.

**50**<sup>+</sup> **telescopic drill stand** with expandable stanchion and drill column using hardened extension modules.



Accessories to the **50**<sup>+</sup> telescopic drill stand include three universal extension modules, flex top, rotatable overhead fastener, adjustment screw and Weka mounting plate.

## 50<sup>+</sup> Telescopic and hand held drill stands

- Drill vertical, horizontal, at any angle or stitch drill without the need of anchoring
- Quick start-up, easy finish and no holes
- Expandable telescopic stanchion and drill column using hardened extension modules
- Crankable telescopic stanchion with toothed rack on both outer and inner tubes
- Flex top with zero adjustment and bolt hole
- Solid high tensile aluminium base plates
- Rotatable overhead fastener

Technical data -	50 <sup>+</sup> telescopic drill stand
Telescopic length (mm) Extension modules (mm)	1850- 2950 130 / 490 / 750
Max drill diameter (mm) Max stroke length (mm)	350 (vertical using <i>BackSupport</i> *) 675
Rotation angle (°) Tilting angle (°)	360 - 70 to + 90 0 to 180
Weight (kg)	56 kg







#### Smart drill stands for professionals

## The 3<sup>rd</sup> generation of drill stands

























#### **Stabilizers**

- 40<sup>+</sup> hand held drill stands
  - Flexsupport<sup>+</sup> attached to floor, wall or ceiling
- 50<sup>+</sup> hand held drill stands
  - Backsupport<sup>+</sup> attached directly to base plate
- ◆ Telescopic length from 800 to 1300 mm

### **Accessories & spare parts**

Drill carriage, drill column, adjustment screw, extension module to inner stanchion tube, Weka and  $\emptyset$  60 mm mounting plates , anchoring kit and spacers are some examples of our compatible accessories and spare parts.

Please contact us for additional product information.





Horizontal drilling using **50**<sup>+</sup> **telescopic drill stand** and Weka core drill motor.



